


STYLE 87G

Yivli İstavroz Mekanik Tee / Grooved Cross Mechanical Tee

Maximum working pressure: 20 bar





Nominal Size (Inches / DN)		Pipe Outside Diameter	Outlet Size	Quik-T™ Dimensions			Hole Diameter Tolerance +2.0mm	Bolts			Weight Kg.	Approvals
Run	Outlet			A	B	C		Qty.	Size	Length		
2" / 50	1¼" / 32	60.3	42.4	76.5	135.0	82.0	44.5	2	M10	57.0	1.96	FM / UL / LPCB
	1½" / 40	60.3	48.3	76.5	135.0	82.0	44.5	2	M10	57.0	1.97	FM / UL / LPCB
2½" / 65	1¼" / 32	76.1	42.4	82.0	150.0	92.0	50.8	2	M12	76.0	2.15	FM / UL / LPCB / VDS
	1½" / 40	76.1	48.3	82.0	150.0	92.0	50.8	2	M12	76.0	2.32	FM / UL / LPCB
3" / 80	1¼" / 32	88.9	42.4	95.0	160.0	95.0	50.8	2	M12	76.0	2.55	FM / UL / LPCB / VDS
	1½" / 40	88.9	48.3	95.0	160.0	94.0	50.8	2	M12	76.0	2.64	FM / UL / LPCB / VDS
4" / 100	2" / 50	88.9	60.3	95.0	160.0	105.0	63.5	2	M12	76.0	2.40	FM / UL / LPCB
	1¼" / 32	114.3	42.4	104.0	187.0	96.0	50.8	2	M12	76.0	2.78	FM / UL / LPCB / VDS
	1½" / 40	114.3	48.3	104.0	187.0	96.0	50.8	2	M12	76.0	2.79	FM / UL / LPCB / VDS
	2" / 50	114.3	60.3	104.0	187.0	107.0	63.5	2	M12	76.0	3.22	FM / UL / LPCB / VDS
5" / 125	2½" / 65	114.3	76.1	104.0	187.0	106.0	69.8	2	M12	76.0	3.57	FM / UL
	3" / 80	114.3	88.9	113.0	187.0	130.0	88.9	2	M12	76.0	5.60	FM / UL
	1¼" / 32	139.7	42.4	119.0	216.0	100.0	50.8	2	M16	89.0	3.98	FM / VDS
	1½" / 40	139.7	48.3	119.0	216.0	100.0	50.8	2	M16	89.0	4.06	FM / VDS
6" OD	2" / 50	139.7	60.3	119.0	216.0	106.0	63.5	2	M16	89.0	4.30	FM / VDS
	2½" / 65	139.7	76.1	119.0	216.0	107.0	69.8	2	M16	89.0	4.60	FM / VDS
	1¼" / 32	165.1	42.4	128.5	245.0	96.0	50.8	2	M16	120.0	4.32	FM / LPCB
	1½" / 40	165.1	48.3	128.5	245.0	96.0	50.8	2	M16	120.0	4.31	FM / LPCB
	2" / 50	165.1	60.3	132.0	245.0	107.0	63.5	2	M16	120.0	4.81	FM / LPCB
6" / 150	2½" / 65	165.1	76.1	129.0	245.0	107.0	69.8	2	M16	120.0	5.27	FM / LPCB
	3" / 80	165.1	88.9	135.5	245.0	140.0	88.9	2	M16	120.0	5.65	FM / UL
	4" / 100	165.1	114.3	137.0	245.0	156.0	114.3	2	M16	120.0	5.70	FM / UL
	1¼" / 32	168.3	42.4	133.0	245.0	96.0	50.8	2	M16	120.0	4.23	FM / UL / LPCB / VDS
	1½" / 40	168.3	48.3	130.5	245.0	96.0	50.8	2	M16	120.0	4.33	FM / UL / LPCB / VDS
8" / 200	2" / 50	168.3	60.3	131.5	245.0	107.0	63.5	2	M16	120.0	4.92	FM / UL / LPCB / VDS
	2½" / 65	168.3	76.1	132.5	245.0	107.0	69.8	2	M16	120.0	5.15	FM / UL / LPCB / VDS
	3" / 80	168.3	88.9	138.5	247.0	140.0	88.9	2	M16	120.0	7.21	FM / UL / VDS
8" / 200	4" / 100	168.3	114.3	139.5	247.0	163.0	114.3	2	M16	120.0	6.24	FM / UL / LPCB
	2½" / 65	219.1	76.1	155.0	320.0	120.0	69.8	2	M20	120.0	6.24	-
	3" / 80	219.1	88.9	161.0	320.0	138.0	88.9	2	M20	120.0	7.63	-
4" / 100	219.1	114.3	161.0	320.0	164.0	114.3	2	M20	120.0	7.79	-	

STYLE 88T

Dişli İstavroz Mekanik Tee / Threaded Cross Mechanical Tee

Maximum working pressure: 20 bar



Nominal Size (Inches / DN)		Pipe Outside Diameter	Outlet Size	Quik-T™ Dimensions			Hole Diameter Tolerance +2.0mm	Bolts		Weight Kg.	Approvals	
Run	Outlet			A	B	C		Qty.	Size			Length
2" / 50	1/2" / 15	60.3	21.3	58.0	135.0	76.0	38.1	2	M10	57.0	1.70	FM / UL / LPCB / VDS
	3/4" / 20	60.3	26.9	58.0	135.0	76.0	38.1	2	M10	57.0	1.74	FM / UL / LPCB / VDS
	1" / 25	60.3	33.7	65.5	135.0	76.0	38.1	2	M10	57.0	1.89	FM / UL / LPCB / VDS
	1 1/4" / 32	60.3	42.4	69.5	135.0	82.0	44.5	2	M10	57.0	1.93	FM / UL / LPCB
	1 1/2" / 40	60.3	48.3	69.5	135.0	82.0	44.5	2	M10	57.0	1.91	FM / UL / LPCB
2 1/2" / 65	1/2" / 15	76.1	21.3	67.0	150.0	92.0	38.1	2	M12	76.0	2.31	FM / UL / LPCB / VDS
	3/4" / 20	76.1	26.9	69.0	150.0	92.0	38.1	2	M12	76.0	2.26	FM / UL / LPCB / VDS
	1" / 25	76.1	33.7	72.0	150.0	92.0	38.1	2	M12	76.0	2.21	FM / UL / LPCB / VDS
	1 1/4" / 32	76.1	42.4	76.0	150.0	92.0	50.8	2	M12	76.0	2.24	FM / UL / LPCB / VDS
	1 1/2" / 40	76.1	48.3	76.0	150.0	92.0	50.8	2	M12	76.0	2.17	FM / UL / LPCB
3" / 80	1/2" / 15	88.9	21.3	71.0	160.0	80.0	38.1	2	M12	76.0	2.50	FM / UL / LPCB / VDS
	3/4" / 20	88.9	26.9	76.0	160.0	80.0	38.1	2	M12	76.0	2.58	FM / UL / LPCB / VDS
	1" / 25	88.9	33.7	77.5	160.0	80.0	38.1	2	M12	76.0	2.59	FM / UL / LPCB / VDS
	1 1/4" / 32	88.9	42.4	87.5	160.0	94.0	50.8	2	M12	76.0	2.58	FM / UL / LPCB / VDS
	1 1/2" / 40	88.9	48.3	87.5	160.0	94.0	50.8	2	M12	76.0	2.59	FM / UL / LPCB / VDS
4" OD	2" / 50	88.9	60.3	90.0	160.0	102.0	63.5	2	M12	76.0	3.07	FM / UL / LPCB
	1 1/2" / 40	108.0	48.3	101.0	181.0	96.0	50.8	2	M12	76.0	3.08	VDS
4" / 100	1/2" / 15	114.3	21.3	87.0	187.0	96.0	38.1	2	M12	76.0	3.08	FM / LPCB / VDS
	3/4" / 20	114.3	26.9	89.0	187.0	96.0	38.1	2	M12	76.0	3.05	FM / LPCB / VDS
	1" / 25	114.3	33.7	92.0	187.0	96.0	38.1	2	M12	76.0	2.95	FM / LPCB / VDS
	1 1/4" / 32	114.3	42.4	104.0	187.0	96.0	50.8	2	M12	76.0	3.07	FM / UL / LPCB / VDS
	1 1/2" / 40	114.3	48.3	104.0	187.0	96.0	50.8	2	M12	76.0	2.90	FM / UL / LPCB / VDS
	2" / 50	114.3	60.3	104.0	187.0	107.0	63.5	2	M12	76.0	3.48	FM / UL / LPCB / VDS
	2 1/2" / 65	114.3	76.1	104.0	187.0	106.0	69.8	2	M12	76.0	4.90	FM / UL
5" / 125	3" / 80	114.3	88.9	112.0	187.0	130.0	88.9	2	M12	76.0	5.61	FM / UL
	1 1/4" / 32	139.7	42.4	118.5	216.0	100.0	50.8	2	M16	89.0	4.26	FM / VDS
	1 1/2" / 40	139.7	48.3	118.5	216.0	100.0	50.8	2	M16	89.0	4.14	FM / VDS
6" OD	2" / 50	139.7	60.3	120.5	211.0	106.0	63.5	2	M16	89.0	4.54	FM / VDS
	1 1/2" / 40	159.0	48.3	124.0	238.0	96.0	50.8	2	M16	120.0	4.48	VDS
6" OD	1 1/4" / 32	165.1	42.4	126.5	245.0	96.0	50.8	2	M16	120.0	4.56	FM / LPCB
	1 1/2" / 40	165.1	48.3	126.5	245.0	96.0	50.8	2	M16	120.0	4.35	FM / LPCB
	2" / 50	165.1	60.3	126.5	245.0	107.0	63.5	2	M16	120.0	5.34	FM / LPCB
	2 1/2" / 65	165.1	76.1	135.0	247.0	107.0	69.8	2	M16	120.0	6.62	FM / LPCB
	3" / 80	165.1	88.9	135.0	245.0	140.0	88.9	2	M16	120.0	6.61	FM / UL
6" / 150	4" / 100	165.1	114.3	143.0	245.0	156.0	114.3	2	M16	120.0	8.20	FM / UL
	1 1/4" / 32	168.3	42.4	133.0	245.0	96.0	50.8	2	M16	120.0	4.50	FM / UL / LPCB / VDS
	1 1/2" / 40	168.3	48.3	133.0	245.0	96.0	50.8	2	M16	120.0	4.49	FM / UL / LPCB / VDS
	2" / 50	168.3	60.3	130.0	245.0	107.0	63.5	2	M16	120.0	5.27	FM / UL / LPCB / VDS
	2 1/2" / 65	168.3	76.1	140.5	245.0	117.0	69.8	2	M16	120.0	6.62	FM / UL / LPCB
8" / 200	3" / 80	168.3	88.9	137.5	247.0	140.0	88.9	2	M16	120.0	6.60	FM / UL / VDS
	4" / 100	168.3	114.3	144.0	247.0	160.0	114.3	2	M16	120.0	8.05	FM / UL / LPCB
	2 1/2" / 65	219.1	76.1	157.5	320.0	120.0	69.8	2	M20	120.0	6.99	-
	3" / 80	219.1	88.9	161.0	320.0	141.0	88.9	2	M20	120.0	7.58	-
	4" / 100	219.1	114.3	171.0	325.0	171.0	114.3	2	M20	120.0	10.65	-