


Geberit Mapress adapter with union nut



Application Purpose

- For sanitary, heating and industrial purposes

Characteristics

- With pressing indicator
- Leaky if unpressed up to dia. 54 mm
- Flat sealed
- Union nut made of brass

Product Details

Product material	Gunmetal (CuSn5Zn5Pb2-C)
Operating temperature with EPDM flat gasket	0–100 °C


Scope Of Delivery

- Seal ring
- EPDM flat gasket
- CIIR black with dia. ≤ 54 mm; EPDM with dia. > 54 mm

Ordering Information

Article no.	dØ [mm]	G ["]	L [cm]	Z [cm]
65081	12	1/2	3,2	0,9
65182	15	1/2	5,1	2,5
65082	15	3/4	3,7	1,1
65083	18	3/4	3,7	1,1
65040	18	1	3,9	1,3
65084	22	1	4	1,1
65044	22	1 1/4	4,3	1,3
65045	22	1 1/2	4,4	1,3
65046	28	1	4	1,3
65085	28	1 1/4	4,4	1,3
65050	28	1 1/2	4,6	1,3
65086	35	1 1/2	4,8	1,3
65051	35	2	4,8	1,2
65087	42	1 3/4	5,2	1,3
65052	42	2	5,4	1,4
65053	42	2 1/4	5,6	1,4
65088	54	2 3/8	5,8	1,5
65054	54	2 1/2	6,3	1,4
65090	76,1	3	9,1	2,5
65091	88,9	3 1/2	9,8	2,4

Geberit Mapress adapter union with male thread



Application Purpose

- For sanitary, heating and industrial purposes

Characteristics

- With pressing indicator
- Leaky if unpressed
- Male thread
- Union nut made of brass

Product Details

Product material	Gunmetal (CuSn5Zn5Pb2-C)
Operating temperature with EPDM flat gasket	0–100 °C

Scope Of Delivery

- Seal ring CIIR black
- EPDM flat gasket

Ordering Information

Article no.	dØ [mm]	R ["]	G ["]	H [cm]	L [cm]
65531	12	3/8	1/2	3,4	5,1
65540	12	1/2	1/2	3,8	5,5
65532	15	1/2	3/4	4,1	6,1
65541	15	3/4	3/4	4,3	6,3
65533	18	1/2	3/4	4,1	6,1
65542	18	3/4	3/4	4,3	6,3
65534	22	1/2	1	4,6	6,7
65543	22	3/4	1	4,7	6,8
65544	22	1	1	4,8	6,9
65535	28	1	1 1/4	5,2	7,5
65536	35	1 1/4	1 1/2	5,4	8
65537	42	1 1/2	1 3/4	5,5	8,5
65538	54	2	2 3/8	6,2	9,7