


Geberit Mapress bend adapter 90° with female thread



Application Purpose

- For heating installations
- For air-conditioning applications
- For sprinkler systems (wet)
- Not suitable for drinking water

Characteristics

- Galvanized
- Leaky if unpressed
- With pressing indicator
- Female thread

Product Details

Product material	Non-alloy steel 1.0034 E 195 (DIN EN 10305)
Elbow	90°


Scope Of Delivery

- Seal ring CIIR black

Ordering Information

Article no.	dØ [mm]	Rp ["]	L [cm]	L1 [cm]	Z [cm]	Z1 [cm]
20552	15	3/8	4,9	4,5	2,9	3,4
20553	15	1/2	4,9	4,8	2,9	3,3
20555	18	1/2	5,3	5,2	3,3	3,7
20557	22	3/4	6,1	6	4	4,4
20558	28	1/2	7,2	6,5	4,9	5
20559	28	1	7,2	6,6	4,9	4,7
20560	35	1 1/4	6,8	7,5	4,2	5,4
20561	42	1 1/2	8	8,4	5	6,3
20562	54	2	10	10,4	6,5	7,8

Geberit Mapress adapter union with male thread



Application Purpose

- For heating installations
- For air-conditioning applications
- For sprinkler systems (wet)
- Not suitable for drinking water

Characteristics

- Galvanized
- Leaky if unpressed
- With pressing indicator
- Male thread
- Removable, flat seal

Product Details

Product material	Non-alloy steel 1.0034 E 195 (DIN EN 10305)
Operating temperature with EPDM flat gasket	0–100 °C


Scope Of Delivery

- Seal ring CIIR black
- EPDM flat gasket

Ordering Information

Article no.	dØ [mm]	R ["]	G ["]	H [cm]	L [cm]
25330	15	1/2	3/4	4,1	6,1
25332	18	1/2	3/4	4,1	6,1
25335	22	3/4	1	4,7	6,8
25329	22	1	1	4,8	6,9
25337	28	1	1 1/4	5,2	7,5
25338	35	1 1/4	1 1/2	5,4	8
25339	42	1 1/2	1 3/4	5,5	8,5
25340	54	2	2 3/8	6,2	9,7

Geberit Mapress adapter union with female thread



Application Purpose

- For heating installations
- For air-conditioning applications
- For sprinkler systems (wet)
- Not suitable for drinking water

Characteristics

- Free from substances that constrain from painting
- Galvanized
- Union nut made of brass
- Leaky if unpressed
- With pressing indicator
- Female thread
- Removable, flat seal

Product Details

Product material	Non-alloy steel 1.0034 E 195 (DIN EN 10305)
Operating temperature with EPDM flat gasket	0–100 °C

Scope Of Delivery

- Seal ring CIIR black
- EPDM flat gasket

Ordering Information

Article no.	dØ [mm]	Rp ["]	G ["]	L [cm]	Z [cm]
25300	15	1/2	3/4	5,8	2,3
25302	18	1/2	3/4	5,8	2,3
25304	22	3/4	1	6,3	2,3
25305	22	1	1	6,6	3
25306	28	1	1 1/4	7,1	3,3
25307	35	1 1/4	1 1/2	7,7	3,5
25308	42	1 1/2	1 3/4	8,2	3,1
25309	54	2	2 3/8	9,5	3,4