

Geberit Mapress connector with union nut



Application Purpose

- For heating installations
- For air-conditioning applications
- For sprinkler systems (wet)
- For radiator connectors
- Not suitable for drinking water

Characteristics

- Galvanized
- Leaky if unpressed
- With pressing indicator
- Union nut nickel-plated
- Flat sealed

Product Details

Product material	Non-alloy steel 1.0034 E 195 (DIN EN 10305)
Operating temperature with EPDM flat gasket	0–100 °C

Scope Of Delivery

- Seal ring CIIR black
- EPDM flat gasket

Ordering Information

Article no.	dØ [mm]	G ["]	diØ [mm]	L [cm]	Z [cm]
25042	15	1/2	10	5,1	2,5
25048	18	1/2	10	5,3	2,6
25049	22	3/4	13	5,4	2,7

Geberit Mapress adapter with union nut



Application Purpose

- For heating installations
- For air-conditioning applications
- For sprinkler systems (wet)
- Not suitable for drinking water

Characteristics

- Galvanized
- Leaky if unpressed
- With pressing indicator
- Union nut made of brass
- Flat sealed

Product Details

Product material	Non-alloy steel 1.0034 E 195 (DIN EN 10305)
Operating temperature with EPDM flat gasket	0–100 °C

Scope Of Delivery

- Seal ring CIIR black
- EPDM flat gasket

Ordering Information

Article no.	dØ [mm]	G ["]	diØ [mm]	L [cm]	Z [cm]
25032	15	3/4	13	3,7	1,1
25033	18	3/4	13	3,7	1,1
25040	18	1	20	3,9	1,1
25034	22	1	20	4	1,1
25044	22	1 1/4	26	4,3	1,3
25035	28	1 1/4	26	4,4	1,3
25050	28	1 1/2	32	4,6	1,3
25036	35	1 1/2	32	4,8	1,3
25051	35	2	42	4,8	1,2
25037	42	1 3/4	39	5,2	1,3
25052	42	2	42	5,4	1,4
25053	42	2 1/4	42	5,6	1,4
25038	54	2 3/8	51	5,8	1,5
25054	54	2 1/2	54	6,3	1,4
25055	54	2 3/4	57	6,3	1,4
25045	76,1	3	73	9,9	3,3
25046	88,9	3 1/2	84	11,1	3,7

Straight unions

Geberit Mapress union



Application Purpose

- For heating installations
- For air-conditioning applications
- For sprinkler systems (wet)
- Not suitable for drinking water

Characteristics

- Galvanized
- Leaky if unpressed
- With pressing indicator
- Removable, flat seal

Product Details

Product material	Non-alloy steel 1.0034 E 195 (DIN EN 10305)
Operating temperature with EPDM flat gasket	0–100 °C

Scope Of Delivery

- Seal rings CIIR black
- EPDM flat gasket

Ordering Information

Article no.	dØ [mm]	G ["]	L [cm]	Z [cm]
25320	15	3/4	6,6	2,6
25321	18	3/4	6,9	2,9
25322	22	1	7,2	3
25323	28	1 1/4	7,7	3,1
25324	35	1 1/2	8,2	3
25325	42	1 3/4	9,5	3,5
25326	54	2 3/8	11,3	4,3