


STYLE 05 LONG RADIUS

Eşit Tee / Equal Tee


Maximum working pressure: 34.5 bar



STYLE 65 SHORT RADIUS

Eşit Tee / Equal Tee

Maximum working pressure: 34.5 bar



| Nominal Size (Inches / DN) | Pipe Outside Diameter | Dimen- sion | | Weight Kg. | Approvals |
|-------------------------------|--------------------------|----------------|--------|-----------------------|-----------|
| | | A | | | |
| 1" / 25 | 33.7 | - | - | - | |
| 1¼" / 32 | 42.4 | - | - | - | |
| 1½" / 40 | 48.3 | - | - | - | |
| 2" / 50 | 60.3 | 82.5 | 0.98 | FM / UL LPCB / VDS | |
| 2½" / 65 | 76.1 | 95.0 | 1.81 | FM / UL LPCB / VDS | |
| 3" / 80 | 88.9 | 108.0 | 2.46 | FM / UL LPCB / VDS | |
| 4" OD | 108.0 | 127.0 | 3.80 | FM / UL VDS | |
| 4" / 100 | 114.3 | 127.0 | 4.00 | FM / UL | |
| 5" OD | 133.0 | 140.0 | 4.64 | VDS | |
| 5" / 125 | 139.7 | 140.0 | 6.63 | FM / UL LPCB / VDS | |
| 6" OD | 159.0 | - | - | - | |
| 6" OD | 165.1 | 165.0 | 8.80 | UL / LPCB | |
| 6" / 150 | 168.3 | 165.0 | 9.15 | FM / UL LPCB / VDS | |
| 8" / 200 | 219.1 | 196.0 | 16.65 | FM / UL LPCB / VDS | |
| 10" / 250 | 273.0 | 229.0 | 36.20 | FM / UL VDS | |
| 12" / 300 | 323.9 | 254.0 | 50.20 | UL | |
| 14" / 350 | 355.6 | 282.0 | 63.50 | - | |
| 16" / 400 | 406.4 | 305.0 | 106.00 | - | |

| Nominal Size (Inches / DN) | Pipe Outside Diameter | Dimen- sion | | Weight Kg. | Approvals |
|-------------------------------|--------------------------|----------------|-------|-----------------------|-----------|
| | | A | | | |
| 1" / 25 | 33.7 | 58.0 | 0.36 | LPCB / VDS | |
| 1¼" / 32 | 42.4 | 70.0 | 0.66 | FM / LPCB VDS | |
| 1½" / 40 | 48.3 | 70.0 | 0.75 | FM / LPCB | |
| 2" / 50 | 60.3 | 70.0 | 0.90 | FM / UL LPCB / VDS | |
| 2½" / 65 | 76.1 | 76.0 | 1.35 | FM / UL LPCB / VDS | |
| 3" / 80 | 88.9 | 85.5 | 1.80 | FM / UL LPCB / VDS | |
| 4" OD | 108.0 | 101.0 | 2.70 | VDS | |
| 4" / 100 | 114.3 | 101.0 | 2.65 | FM / UL | |
| 5" OD | 133.0 | - | - | - | |
| 5" / 125 | 139.7 | 124.0 | 5.0 | FM / UL LPCB / VDS | |
| 6" OD | 159.0 | 140.0 | 6.88 | VDS | |
| 6" OD | 165.1 | 140.0 | 8.23 | FM / UL LPCB / VDS | |
| 6" / 150 | 168.3 | 140.0 | 7.26 | FM / UL LPCB / VDS | |
| 8" / 200 | 219.1 | 174.0 | 13.63 | FM / UL LPCB / VDS | |
| 10" / 250 | 273.0 | - | - | - | |
| 12" / 300 | 323.9 | - | - | - | |
| 14" / 350 | 355.6 | - | - | - | |
| 16" / 400 | 406.4 | - | - | - | |