



VIZA.EX3620 Fittings, Grooved and Plain End

[Page Bottom](#)

Fittings, Grooved and Plain End

[See General Information for Fittings, Grooved and Plain End](#)

MODGAL METAL (99) LTD

EX3620

Z H R INDUSTRIAL ZONE
PO BOX 63
12000 ROSH PINA, ISRAEL

The following fittings are intended for use with Modgal's Listed rubber gasketed fittings:

Model	Type	Size In.	Rated Pressure (psig)
Style 02	End Caps	1-1/4 to 8	500
Style 02	End Cap	273 mm	175
Style 02	End Cap	324 mm	175
Style 02	End Cap	42, 48, 60, 76, 89, 114, 165, 168, 219, 273, 324	—
Style 02D	End Caps	3, 4, 6, 8,	500
	with Drain		
Style 02D	End Caps	108 mm, 159 mm, 165.1 mm	300
	with Drain		
Style 04	45 Degree Elbow	1-1/4 , 1-1/2, 2, 2-1/2,	500
		3, 4, 6, 8, 76.1 mm, 165.1 mm	
Style 05	Tees	1-1/4, 1-1/2, 2, 2-1/2, 3,	500
		4, 6, 8	
		10	400
		76.1 mm, 108 mm, 159 mm	250
Style 05	Tee	324 mm	175
Style 05	Tee	42, 48, 60, 76, 89, 114, 140, 165, 168, 219, 273, 324	—
Style 06	90 Degree Elbow	1-1/2, 2, 2-1/2,	500
		3, 4, 5, 6, 8	
		10	400
Style 06	90 Degree Elbow	42, 48, 60, 76, 89, 114, 165, 168, 219, 273, 324	—
Style 06	90 Degree Elbow	76.1 mm, 108 mm, 159 mm	250
Style 06	Elbow 90	42 mm	500
Style	Elbow 90	324 mm	175

06			
Style 06D	90 Degree Drain	3, 4, 6	500
	Elbow		
Style 15	Concentric Reducers	1-1/2x1-1/4, 2x1-1/2,	500
		3x2, 3x2-1/2, 4x2, 4x3, 6x4,	
		6x4, 8x4, 8x6, 76 mm x 2in.	
Style 15	Reducer	114x76 mm	500
Style 15	Reducer	76x60 mm	500
Style 15	Reducer	60x34, 42, 48, 76x34, 42, 48, 60, 89x34, 48, 60, 76, 114x34, 48, 60, 76, 89	—
Style 55	Reducing Tees	2-1/2x2-1/2x2,	500
		3x3x2, 4x4x2,	
		4x4x2-1/2, 4x4x3,	
		6x6x2, 6x6x3, 6x6x4	
Style 55	Reducing Tees	60x48, 89x34, 48, 60, 76, 114x34, 60, 76, 89	—
Style 24	Grooved by Female	1-1/2x1, 2x1-1/2	300
	Thread Adaptors		
Style 25	Sprinkler Adaptors	1x1/2, 1x3/4	300
Style 55	Reducing Tee	114x114x76 mm	500
Style 55	Reducing Tee	76x76x60 mm	500
Style 26	Reducing Elbows	1-1/2x1/2, 1-1/2x3/4,	300
		1-1/2x1, 2x1/2, 2x3/4, 2x1	
Style 28	Grooved by Male	1-1/2x1-1/2, 2x2	300
	Thread Adaptors		
Style 55	Reducing Tee	141.3 mm x 60.3 mm, 88.9 mm, 114.3 mm	500
		168.3 mm x 60.3 mm, 73.0 mm, 88.9 mm, 114.3 mm, 141.3 mm	
		219.1 mm x 60.3 mm, 88.9 mm, 114.3 mm, 141.3 mm, 168.3 mm	
Style 45	Cross	60.3 mm, 76.1 mm, 88.9 mm, 114.3 mm, 141.3 mm, 168.3 mm	500
		165.1 mm, 219.1 mm, 273.0 mm, 323.8 mm	
Style 15	Grooved Concentric Reducer	141.3 mm x 88.9 mm, 114.3 mm	500
		168.3 mm x 33.4 mm, 60.3 mm, 73.0 mm, 88.9 mm, 114.3 mm, 141.3 mm	
		219.1 mm x 73.0 mm, 88.9 mm, 114.3 mm, 141.3 mm, 168.3 mm	
Style 91	Flange Adapter	60.3 mm, 73.0 mm, 76.1 mm, 88.9 mm, 114.3 mm, 168.3 mm, 165.1 mm, 219.1 mm	300
Style 91	Flange Adapter	273.0 mm, 323.8 mm	225

Style 64	45 Degree Elbow	42.2 mm, 48.3 mm, 60.3 mm, 73.0 mm, 76.1 mm, 88.9 mm, 114.3 mm, 141.3 mm, 168.3 mm, 165.1 mm, 219.1 mm, 273.0 mm, 323.8 mm	500
Style 66	90 Degree Short Elbow	60.3 mm, 88.9 mm, 114.3 mm, 139.7 mm, 168.3 mm, 165.1 mm, 219.1 mm	300
Style 65	Short Tee	60.3 mm, 88.9 mm, 114.3 mm, 139.7 mm, 168.3 mm, 165.1 mm, 219.1 mm	300
Style 06M	90 Degree Elbow	1-1/4, 1-1/2, 2, 2-1/2, 3 OD, 3, 4, 5, 5-1/2 OD, 6, 6-1/2 OD, 8	500
Style 66M	90 Degree Short Elbow	2-1/2	300
Style 64M	45 Degree Elbow	2-1/2, 5	500
Style 05M	Tee	5	500
Style 65M	Short Tee	2-1/2	300
Style 15M	Grooved Concentric Reducer	2-1/2	500
Style 02M	Cap	2-1/2, 5	500

Last Updated on 2011-02-03

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".